INSULATED BEVERAGE SERVERS

Keep beverages hot or cold for hours! Perfect for front or back-of-house use. One-piece, seamless double-wall polyethylene construction and foamed-in-place polyurethane insulation ensures years of dependable service and prevents liquids from seeping between walls. Molded-in mounting plates prevent latches from pulling out. Drip-proof recessed spigot allows for easy access and can be easily adjusted without tools.

Wide service opening accommodates larger cups and/or coffee pots when units are stacked on a riser. Sta-stack interlocking allows for stable stacking. Self-adhesive beverage label set included with each unit.

UC250 and UC500 covered by U.S. Patent D 403,917. UC1000 covered by U.S. Patent D 403,916.



Vent Cap
Equalizes pressure. Makes opening the container much easier.

E-Z Grip Molded-in Handles
For comfortable, safe transporting.

Recessed Faucet
Accommodates larger cups. Allows even dispensing and eliminates drips. Two positions: one for continuous pouring and one for individual dispensing.

Molded-in Metal Backing Plates
Prevents latches from breaking away from the container.



Ultra Camtainers®
Feature wide nylon latches which are easy to open and close with one hand.

Camtainers®
Feature sturdy plastic latches that secure lids tightly and will never rust.

Stack beverage servers during storage and transporting to save space.

Stacking options:
- 100LCD with 100LCD
- All 250, 350 and 500 units
- UC1000 and 1000LCD

Hot

	Starting Temperature	1 hr.	2 hrs.	3 hrs.	4 hrs.
250LCD	188˚F	184˚F	179˚F	174˚F	170˚F
UC250	190˚F	186˚F	183˚F	179˚F	176˚F

Cold

	Starting Temperature	1 hr.	2 hrs.	3 hrs.	4 hrs.
250LCD	33.5˚F	35˚F	36˚F	38˚F	39˚F
UC250	33˚F	33.5˚F	34˚F	35˚F	36˚F